

SHACKLES



Screw Pin Anchor Bow Shackle

Federal Specification RR-C-271D, Type IVA, Grade A, Class 2

- (6:1 WLL) Galvanized, dimensions approx.
- Forged – Quenched and Tempered, Alloy Pins.
- Meets or exceeds all requirements of ASME B30.26."

NOMINAL SIZE (IN.)	WORKING LOAD LIMIT (tonne)
3/16	1/3
1/4	1/2
5/16	3/4
3/8	1
7/16	1-1/2
1/2	2
5/8	3-1/4
3/4	4-3/4
7/8	6-1/2
1	8-1/2
1-1/8	9-1/2
1-1/4	12
1-3/8	13-1/2
1-1/2	17
1-3/4	25
2	35
2-1/2	55

Safety Anchor Bow Shackle

Federal Specification RR-C-271D, Type IVA, Grade A, Class 3

- (6:1 WLL) Galvanized, dimensions approx.
- Forged – Quenched and Tempered, Alloy Pins.
- To assure traceability, "Yellow Pin" shackles are embossed to exceed ASME B30.26 requirements

NOMINAL SIZE (IN.)	WORKING LOAD LIMIT (tonne)
1/4	1/2
5/16	3/4
3/8	1
7/16	1-1/2
1/2	2
5/8	3-1/4
3/4	4-3/4
7/8	6-1/2
1	8-1/2
1-1/8	9-1/2
1-1/4	12
1-3/8	13-1/2
1-1/2	17
1-3/4	25
2	35



Long Reach Screw Pin Shackle

- Design factor of 5:1
- Meets the requirements of ASME B30.26
- Alloy Steel
- WLL forged on body
- Durable orange powder coated finish

NOMINAL SIZE (IN.)	WORKING LOAD LIMIT (lbs.)
5/8	7,000
3/4	10,000
1	19,000
1-1/4	28,000
1-1/2	34,000
1-3/4	50,000

SASKATOON

3235 Millar Avenue, Saskatoon SK S7K 5Y3 FAX: (306) 249-4374
Ph: (306) 242-7073 Toll Free: 1-800-242-7073

REGINA

125 Henderson Drive, Regina SK S4N 5W4 FAX: (306) 352-9112
Ph: (306) 352-7073 Toll Free: 1-800-242-7073