

NORTHERN STRANDS IS A PREMIUM SUPPLIER OF PROGRESSIONER CABLES

Die Drawn - 6 Strand

Applications: Surface Mining, Construction, Logging, Oil Fields, Winch Lines, Car Pullers/Progressioner.

CABLE COMPOSITION AND BENEFITS

Northern Strands uses 6 x 26 Warrington Seale Compacted Strand IWRC. This cable has a smoother bearing surface at the strand crowns and an increase in minimum breaking force over round strand rope of the same diameter and classification.

GENERAL CHARACTERISTICS

Compacted cables have more load bearing capacities than the standard cables with same diameters. Abrasion is less and usage lives are longer as they contact the reel surfaces in a larger area.

- High Strength to Diameter Ratio
- · High Resistance to Abrasion
- · High Resistance to Crushing
- · Better Fatigue Resistance
- Equals Better Service Life

WEIGHTS AND BREAKING LOADS TABLE			
DIA. INCHES	WEIGHT LBS/FT	BREAKING STRENGTH LBS	CONSTRUCTION
3/4"	1.09	64,800	6 X 26
7/8"	1.49	87,600	6 X 26
1"	1.94	113,800	6 X 26 & 6 X 31
1 1/8"	2.46	143,000	6 X 31
1 1/4"	3.03	175,800	6 X 31