

New

3100-BOS-R1 System



LEADING TECHNOLOGY IN WIRE ROPE APPLICATOR SYSTEMS.

A NEW DESIGN MAKING WIRE ROPE LUBRICATION QUICK & EASY WITHOUT THE MESS.

3100-BOS SYSTEM

Cable Size Range: 0.5" (12.7mm) to 3." (77mm)

The 3100-BOS-R1 System is designed to apply thick oils / semi fluids & soft greases that are self penetrating.

3100-BOS HOUSING



ADVANTAGES


- Easy to use.
- Lubricates wire ropes at speeds of 250 Ft./ Min.
- One brush size fits a range of rope sizes. Eliminates the need for a rubber seal for every size of wire rope.
- Wire rope deformities can be run through the unit.
- Wire ropes can run through the unit at any angle.
- The same pump fits all sizes of containers from a drum to a pail.

3100-BOS-R1 SYSTEM



OPTIONAL Case #1620

Lid Supplied 16-20kg



3100-BOS-R1 System

FIGHT CORROSION with the NEW 3100-BOS SYSTEM

BOS SYSTEM PROTECTION




(3) Sizes Available



4100-BOS
4.5" Cable

3100-BOS
3" Cable

2100-BOS
1 5/8" Cable



CoreLube Equipment
Cable Lubrication & Cleaning Specialist

Phone: 403-529-9645 Fax: 403-527-1369

E-mail: sales@corelube.com

www.corelube.com