

**CROSBY  
RIGGING  
PRODUCTS**

# SLEEVES



### Aluminum Duplex Sleeves - Generally used with galvanized wire

Cable Size	Wt./100lbs	Length	Depth	Width	O.D After Swage
1/16"	0.10	3/8	11/64	1/4	0.187"
3/32"	0.30	1/2	9/32	13/32	0.281"
1/8"	0.66	5/8	11/32	1/2	0.312"
5/32"	0.88	11/16	3/8	9/16	0.375"
3/16"	1.61	7/16	2	1/32	0.437"
1/4"	2.8	1-1/8	17/32	13/16	0.563"
5/16"	4.6	1-1/4	11/16	1-1/32	0.687"
3/8"	5.9	1-7/16	3/4	1-5/32	0.812"
7/16"	12	1-11/16	15/16	1-7/16	1.000"
1/2"	17	2	1-1/16	1-5/8	1.120"



### Aluminum Wire Rope Stops- Generally used with galvanized wire

Cable Size	Wt./100lbs	Length	Depth	Width	O.D After Swage
1/16"	0.06	1/4	3/32	0.187"	0.187"
3/32"	0.25	11/32	1/8	0.245"	0.281"
1/8"	0.24	11/32	5/32	0.245"	0.312"
5/32"	0.38	7/16	3/16	0.325"	0.375"
3/16"	0.35	7/16	7/32	0.325"	0.437"
1/4"	2.06	11/16	9/32	0.508"	0.563"
5/16"	1.74	11/16	3/8	0.508"	0.687"



### Copper Oval Sleeves - Generally used with stainless steel wire

Cable Size	Wt./100lbs	Length	Depth	Width	O.D After Swage
1/16"	0.3	25/64	11/64	1/4	0.190"
3/32"	0.65	29/64	15/64	3/8	0.265"
1/8"	1.6	9/16	21/64	1/2	0.353"
5/32"	2.3	5/8	3/8	19/32	0.390"
3/16"	5.1	7/8	7/16	43/64	0.475"
1/4"	7.5	1-1/8	13/16	1/2	0.585"
5/16"	11.8	1-1/8	2 1/32	1-1/64	0.730"
3/8"	17	1-1/2	23/32	1-1/8	0.795"



### Copper Wire Rope Stops - Generally used with stainless steel wire

Cable Size	Wt./100lbs	Length	Depth	Width	O.D After Swage
1/16"	0.20	13/64	5/64	0.182"	0.187"
3/32"	0.80	21/64	7/64	0.261"	0.281"
1/8"	0.80	21/64	5/32	0.261"	0.312"
5/32"	1.3	27/64	3/16	0.350"	0.375"
3/16"	1.2	27/64	7/32	0.350"	0.437"
1/4"	6	21/32	9/32	0.600"	0.563"
5/16"	9	21/32	5/16	0.600"	0.687"