

WEB & ROUND SLINGS

Product listing

UNITEX BRAND SUPPLIED BY NORTHERN STRANDS.



POLYESTER WEB SLINGS

- 1" 2 ply from 3' up to 12' WLL 3200lbs Vertical
- 2" 2 ply from 2' up to 20' WLL 6400lbs Vertical
- 3" 2 ply from 4' up to 20' WLL 8600lbs Vertical
- 4" 2 ply from 4' up to 20' WLL 11500lbs Vertical

All other sizes and configurations available upon request. All eyes have a protective covering. All eyes are tapered. Endless web slings.



POLYESTER ROUND SLINGS (DOUBLE SLEEVED)

- 3,000lbs Vertical WLL, Purple sleeve, up to 20'
- 6,000lbs Vertical WLL, Green sleeve, up to 20'
- 9,000lbs Vertical WLL, Yellow sleeve, up to 20'
- 12,000lbs Vertical WLL, Tan sleeve, up to 20'
- 14,000lbs Vertical WLL, Red sleeve, up to 20'
- 17,000lbs Vertical WLL, Brown, up to 20'
- 21,000lbs Vertical WLL, Blue, up to 20'
- 23,000lbs Vertical WLL, Blue, up to 20'
- 26,000lbs Vertical WLL, Orange, up to 20'
- 32,000lbs Vertical WLL, Grey, up to 20'
- 40,000lbs Vertical WLL, Orange, up to 20'
- 54,000lbs Vertical WLL, Brown, up to 20'
- 68,000lbs Vertical WLL, Olive, up to 20'
- 90,000lbs Vertical WLL, Black, up to 20'

Other sizes and lengths available upon request. All round slings have hidden I.D. tag. Up to 9,000lbs

SHACKLES



Screw Pin Anchor Bow Shackle

Federal Specification RR-C-271D, Type IVA, Grade A, Class 2

- (6:1 WLL) Galvanized, dimensions approx.
- Forged – Quenched and Tempered, Alloy Pins.
- Meets or exceeds all requirements of ASME B30.26."

NOMINAL SIZE (IN.)	WORKING LOAD LIMIT (tonne)
3/16	1/3
1/4	1/2
5/16	3/4
3/8	1
7/16	1-1/2
1/2	2
5/8	3-1/4
3/4	4-3/4
7/8	6-1/2
1	8-1/2
1-1/8	9-1/2
1-1/4	12
1-3/8	13-1/2
1-1/2	17
1-3/4	25
2	35
2-1/2	55

Safety Anchor Bow Shackle

Federal Specification RR-C-271D, Type IVA, Grade A, Class 3

- (6:1 WLL) Galvanized, dimensions approx.
- Forged – Quenched and Tempered, Alloy Pins.
- To assure traceability, "Yellow Pin" shackles are embossed to exceed ASME B30.26 requirements

NOMINAL SIZE (IN.)	WORKING LOAD LIMIT (tonne)
1/4	1/2
5/16	3/4
3/8	1
7/16	1-1/2
1/2	2
5/8	3-1/4
3/4	4-3/4
7/8	6-1/2
1	8-1/2
1-1/8	9-1/2
1-1/4	12
1-3/8	13-1/2
1-1/2	17
1-3/4	25
2	35



Long Reach Screw Pin Shackle

- Design factor of 5:1
- Meets the requirements of ASME B30.26
- Alloy Steel
- WLL forged on body
- Durable orange powder coated finish

NOMINAL SIZE (IN.)	WORKING LOAD LIMIT (lbs.)
5/8	7,000
3/4	10,000
1	19,000
1-1/4	28,000
1-1/2	34,000
1-3/4	50,000

SNATCH BLOCKS

Rigging Blocks

- Forged Alloy Heat Treated Hooks
- Alloy treated hooks and shackles
- Locking feature available to prevent rotation of rope.
- All Blocks open for easy wire installation



Snatch Block (Single)

Wire size	Sheave	Qty/box	Wt. lbs	WLL 4:1
5/16"-3/8"	3"	5	5	2 ton
3/8"-1/2"	4 1/2"	4	12	4 ton
5/8"-3/4"	6"	2	27	8 ton
5/8"-3/4"	8"	1	37	8 ton



Snatch Block (Single)

Wire size	Sheave	Qty/box	Wt. lbs	WLL 4:1
5/16"-3/8"	3"	5	5	2 ton
3/8"-1/2"	4 1/2"	4	12	4 ton
5/8"-3/4"	6"	2	27	8 ton
5/8"-3/4"	8"	1	37	8 ton



Snatch Block (Double)

Wire size	Sheave	Qty/box	Wt. lbs	WLL 4:1
3/8"-1/2"	4 1/2"	2	20	4 ton
5/8"-3/4"	6"	2	49	12 ton
5/8"-3/4"	8"	1	59	12 ton



Snatch Block (Double)

Wire size	Sheave	Qty/box	Wt. lbs	WLL 4:1
3/8"-1/2"	4 1/2"	2	20	4 ton
5/8"-3/4"	6"	2	49	12 ton
5/8"-3/4"	8"	1	59	12 ton